

AMENDED CLAIMS

[Received by the International Bureau on 12 May 2005 (12.05.2005) :
original claims 1, 8 and 12 amended ; original claim 13 cancelled (2 pages)]

1. A record carrier comprising
 - a data area (22) for storing data in the form of marks, in which the data is encoded by means of a channel code, wherein a parameter of the channel code is controlled so as to introduce a predetermined run length distribution in the marks on the record carrier, thereby introducing first information relating to a watermark, and
 - a non-data area (21,23) comprising second information comprising picture and/or text information relating to a watermark,the first and the second information forming the watermark.
- 10 2. A record carrier as claimed in claim 1, wherein the first and the second information forming the watermark (34,36) are orientated with respect to each other.
3. A record carrier as claimed in claim 2, wherein the first and the second information is orientated with respect to each other using position information (54) present in the a non-data area.
- 15 4. A record carrier as claimed in claim 2 or 3, wherein the record carrier further comprises angle information indicating a predetermined angle between the first information and the second information.
- 20 5. A record carrier as claimed in claim 4, wherein the angle information is used as authentication information.
6. A record carrier as claimed in claim 1 or 2, wherein the non-data area is an inner-ring area (21) and/or an outer-ring area (23).
- 25 7. A record carrier as claimed in claim 1 or 2, wherein the non-data area is a graphics band, text band, matrix band or identification band.

8. A record carrier as claimed in claim 1 or 2, the data area comprising a pattern of substantially parallel tracks, wherein the predetermined run length distribution is correlated from track to track, so that the first information is visually detectable.
- 5 9. A record carrier as claimed in claim 1 or 2, wherein the first information is non-visually detectable.
10. A record carrier as claimed in claim 1 or 2, in which the channel code is the EFM channel code as used for the CD Digital Audio disc, wherein the parameter is the
10 choice of merging bits.
11. A record carrier as claimed in claim 1 or 2, wherein the parameter is the choice between channel words for information words from alternative tables, for example, information words 1 up to and including 88 in the EFM+ channel code as used in DVD, or
15 the choice between sync words or the choice between states.
12. A method of providing a watermark on a record carrier, the method comprising the steps of:
- receiving uncoded data,
 - 20 - receiving first information relating to the watermark, which first information is to be provided in the encoded data,
 - receiving second information comprising picture and/or text information relating to the watermark, which second information is to be provided in a non-data area,
 - encoding the uncoded data to encoded data by means of a channel code, in which a
25 parameter of the channel code is controlled under the influence of the first information relating to the watermark for introducing a predetermined run length distribution in the marks on the record carrier,
 - storing the encoded data on the record carrier,
 - storing the second information in the non-data area.